

# TEMPORARY ENERGY FOR YOUR NEXT PROJECT

Easily make the switch to emission free with a Greener battery

# EASILY EMISSION FREE

	 281	 336	 422	 562
<b>Power</b>	225 kVA	318 kVA	318 kVA	225 kVA
<b>Capacity</b>	281 kWh	336 kWh	422 kWh	562 kWh
<b>Dimensions (LxBxH)</b>	2x 2000 × 1600 × 1200 mm	10 ft. container 2990 x 2440 x 2590 mm	10 ft. container 2990 x 2440 x 2590 mm	3x 2000 × 1600 × 1200 mm
<b>Weight</b>	1x 3000 kg capacity, 1x 2300 kg inverter	8200 kg	8700 kg	2x 3000 kg capacity, 1x 2300 kg inverter
<b>Input</b>	125A CEE (Input power till 225 kVA possible through output)	Powerlock 400A	Powerlock 400A	125A CEE (Input power till 225 kVA possible through output)
<b>Output</b>	Powerlock 400A	2x Powerlock 400A and 63A CEE	2x Powerlock 400A and 63A CEE	Powerlock 400A
<b>Frequency</b>	50 Hz	50/60 Hz	50/60 Hz	50 Hz
<b>Voltage AC</b>	400V	400V	400V	400V
<b>Outside temperature</b>	-25°C to +45°C	-20°C to +40°C	-20°C to +40°C	-25°C to +45°C
<b>IP rating</b>	IP55	IP54	IP54	IP55
<b>24/7 Monitoring</b>	Yes	Yes	Yes	Yes
<b>Emergency stop</b>	Yes	Yes	Yes	Yes
<b>Transport</b>	ADR 9	ADR 9	ADR 9	ADR 9
<b>Norms and standards</b>	IEC 62933-5-2, IEC 62619, others on request	IEC 62619, others on request	IEC 62619, others on request	IEC 62933-5-2, IEC 62619, others on request